

Mensaje Log

Escribe un mensaje de diagnóstico en el log con un nivel específico.

Detener Proceso

Detiene un proceso específico.

Listar Procesos

Obtiene la lista de todos los procesos en ejecución.

Último Estado

Obtiene el estado de último comando ejecutado.

Control de ventanas – Minimizar

Minimiza la ventana o navegador que abrimos con Rocketbot.

Subir Archivo

Subir archivo a un input de tipo file.

Mover hasta elemento

Se desplaza hasta un elemento específico de la web.

Obtener Atributo

Obtiene un valor de atributo específico de un elemento.

Obtener URL actual

Obtiene la URL de la página cargada actualmente en el navegador abierto.

Filtros Email

ALL

All messages in the mailbox.

ANSWERED

Messages with the \Answered flag set.

BCC

Messages that contain the specified string in the envelope structure's BCC field.

BEFORE

Messages whose internal date (disregarding time and timezone) is earlier than the specified date.

BODY

Messages that contain the specified string in the body of the message.

CC

Messages that contain the specified string in the envelope structure's CC field.

DELETED

Messages with the \Deleted flag set.

DRAFT

Messages with the \Draft flag set.

FLAGGED

Messages with the \Flagged flag set.

FROM

Messages that contain the specified string in the envelope structure's FROM field.

HEADER

Messages that have a header with the specified field-name (as defined in [RFC-2822]) and that contains the specified string in the text of the header (what comes after the colon). If the string to search is zero-length, this matches all messages that have a header line with the specified field-name regardless of the contents.

KEYWORD

Messages with the specified keyword flag set.

LARGER

Messages with an [RFC-2822] size larger than the specified number of octets.

NEW

Messages that have the \Recent flag set but not the \Seen flag. This is functionally equivalent to "(RECENT UNSEEN)".

NOT

Messages that do not match the specified search key.

OLD

Messages that do not have the \Recent flag set. This is functionally equivalent to "NOT RECENT" (as opposed to "NOT NEW").

ON

Messages whose internal date (disregarding time and timezone) is within the specified date.

OR

Messages that match either search key.

RECENT

Messages that have the \Recent flag set.

SEEN

Messages that have the \Seen flag set.

SENTBEFORE

Messages whose [RFC-2822] Date: header (disregarding time and timezone) is earlier than the specified date.

SENTON

Messages whose [RFC-2822] Date: header (disregarding time and timezone) is within the specified date.

SENTSINCE

Messages whose [RFC-2822] Date: header (disregarding time and timezone) is within or later than the specified date.

SINCE

Messages whose internal date (disregarding time and timezone) is within or later than the specified date.

SMALLER

Messages with an [RFC-2822] size smaller than the specified number of octets.

SUBJECT

Messages that contain the specified string in the envelope structure's SUBJECT field.

TEXT

Messages that contain the specified string in the header or

body of the message.

TO

Messages that contain the specified string in the envelope structure's TO field.

UID

Messages with unique identifiers corresponding to the specified unique identifier set. Sequence set ranges are permitted.

UNANSWERED

Messages that do not have the \Answered flag set.

UNDELETED

Messages that do not have the \Deleted flag set.

UNDRAFT

Messages that do not have the \Draft flag set.

UNFLAGGED

Messages that do not have the \Flagged flag set.

UNKEYWORD

Messages that do not have the specified keyword flag set.

UNSEEN

Messages that do not have the \Seen flag set.